

PLEASE PUBLISH THURSDAY, August 8, 2024

NOTICE FOR BID #25-03

The Board of Pontotoc County Commissioners will receive sealed bids to construct and install a wildland brush truck for the Stonewall VFD. This bid will open on August 26, 2024, at the Board of County Commissioners meeting. Bid specification forms may be obtained at the County Commissioners Office, 100 W 13<sup>th</sup> Street, Room 133, Ada, Oklahoma, or on the County website at [pontotoc.okcounties.org](http://pontotoc.okcounties.org). The Board of County Commissioners reserves the right to reject or accept any or all bids. County bid forms must be used, signed, and notarized. Call the County Commissioners Office at 580.332.8977 for any questions.

Pontotoc

County, Oklahoma

**COUNTY PURCHASING OFFICE**

Pontotoc County Clerk

County Court House

301 S Broadway

Ada, Oklahoma

Phone Number +1 (580) 332-1425

**Invitation to Bid**

PLEASE REVIEW TERMS AND CONDITIONS ON REVERSE SIDE  
RELATING TO SUBMISSION OF THIS BID.  
Notarized Affidavit completions and signature required on reverse side.

Date Issued Aug 5, 2024

Page 1 of 7

**BID NUMBER**

#25-03

**BID CLOSING DATE AND HOUR**

August 26, 2024 9:00 AM

**REQUIRED DELIVERY DATE**

(Days after award of Purchase Order)

**TERMS**

**Date of Delivery**

| ITEM | QUANTITY | UNIT OF ISSUE | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | UNIT PRICE | TOTAL |
|------|----------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------|
|      |          |               | Construct and install a wildland brush truck.<br><br>Specifications for bid are attached.<br><br>Department: Pontotoc County Commissioners for the Stonewall VFD<br>Office Hours: 8:00 AM - 4:00 PM<br>Contact: Chief Danny Summers<br>Telephone: 580.310.5916<br>Return Bids To: Pontotoc County Clerk<br>301 S Broadway * Ada, OK 74820 or<br>PO Box 1425 *Ada, OK 74821-1425<br><br>Instructions:<br>1. Please write sealed Bid #25-03 on the outside of the envelope.<br><br>2. Vendor's bid amount must be listed on the front of this form.<br><br>3. Invitation to Bid form must be notarized and original bid form submitted.<br><br>4. Please verify notarization has been correctly and fully executed.<br>Failure to do so will result in rejection of bid. See item #7 under Terms and Conditions.<br><br>The Board of Pontotoc County Commissioners reserve the right to accept or reject any or all bids. |            |       |

**TERMS and CONDITIONS**

1. Sealed bids will be opened in the Commissioner's Conference Room, Pontotoc  
County Courthouse, Ada, Oklahoma, at the time and date shown on the invitation to bid form.
2. Late bids will not be considered. Bids must be received in sealed envelopes (one to an envelope) with bid number and closing date written on the outside of the envelope.
3. Unit prices will be guaranteed correct by the bidder.
4. Firm prices will be F.O.B. destination.
5. Purchases by Pontotoc County, Oklahoma, are not subject to state or federal taxes.
6. This bid is submitted as a legal offer and any bid when accepted by the County constitutes a firm contract.
7. Oklahoma laws require each bidder submitting a bid to a county for goods or services to furnish a notarized sworn statement of non-collusion. A form is supplied below.
8. Bids will be firm until \_\_\_\_\_ (Date)

AFFIDAVIT: I, the undersigned, of lawful age, being first duly sworn on oath say the he (she) is the agent authorized by the bidder to submit the above bid. Affiant further states that the bidder has not been a party to any collusion among bidders in restraint of freedom of competition by agreement to bid at a fixed price or to refrain from bidding; or with any state official or employee as to quantity; quality or price in the prospective contract or any other terms of said prospective contract; or in any discussions between bidders and any state official concerning exchange of money or other thing of value for special consideration in the letting of a contract; that the bidder/contractor has not paid, given or donated or agreed to pay, give or donate to any officer or employee of the State of Oklahoma (or other entity) any money or other thing of value, either directly or indirectly in the procuring of the award of a contract pursuant to this bid.

Subscribed and sworn before this \_\_\_\_\_ day  
of \_\_\_\_\_, 20 \_\_\_\_\_ (SEAL)

Firm: \_\_\_\_\_

My commission expires \_\_\_\_\_ Signed by: \_\_\_\_\_  
(Manual Signature of Undersigned)

Address: \_\_\_\_\_ Phone: \_\_\_\_\_

\_\_\_\_\_  
NOTARY PUBLIC (CLERK OR JUDGE) Zip: \_\_\_\_\_

*In accordance with 62 O.S. § 310.9*

NOTE: Other terms and conditions can be added at the discretion of the county officers.

**Specifications:** It is intent of these specifications to describe equipment and installation for construction of a wildland brush truck for the Stonewall Fire Department. This equipment is to be installed on a 2024 Ford F450 4 wheel drive truck equipment for firefighting. The ultimate goal of these specifications are for the bidder to provide the Stonewall Fire Department with a wildland firefighting truck that is safe, functional and ready to put into service as a firefighting apparatus.

**Stonewall Fire Department Will Furnish the Following:**

- 2024 F450 ,4 wheel drive truck .

**Bidder** state whether or not your bid complies with the specifications.

**Bidder** list Brand, Model Number and other variations on all equipment to be furnished and installed on the Vendor's Statement. ALL ITEMS TO BE BID AS INSTALLED.

**Bidder** American made products are preferred

| DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | YES | NO |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|
| <p><b>FIRE BED.</b><br/>Steel flat bed , 8' wide by 9'4" long and has 2- 24"wide man wells behind cab.Painted (BLACK) with all DOT lighting. Rear side will be at a 45deg angle<br/>A winch will be on the rear of the apparatus will be adequately mounted so that a 16,000lb winch will be mounted for pulling the vehicle if it become stuck.The winch stalled be installed to manufactures guidelines.<br/>Bed must have headache rack with steel plate to mount light bar.</p> |     |    |
| <p><b>FRONT BUMPER</b></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                          |     |    |
| <p>Front Bumper to be a complete replacement bumper with full brush guard and tow hooks. Bumper to be powder coated black. Two bumper mounted sprayers, mounted on each corner of front bumper. Installed with electric valve with controlled from cab. Must have drains valves for sub-freezing weather.</p>                                                                                                                                                                       |     |    |
| <p>Bumper to be designed and constructed to accommodate a 16,000 pound or larger, electric recovery winch with both wired and wireless remote control. winches shall be installed in bumper with the manufacturer's recommended maximum amount of cable rated for the winch capacity and shall have fairlead, a hook and a block. The winch shall be installed in accordance with all manufactures' guidelines regarding attachment and electrical supply.</p>                      |     |    |
| <p><b>TOOL BOXES</b></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                            |     |    |
| <p>One tool box 60" long, 20" depth, 36" height with 1 shelf inside. Driver side</p>                                                                                                                                                                                                                                                                                                                                                                                                |     |    |
| <p>One tool box 48" long, 20" depth, 18" height , on passenger side</p>                                                                                                                                                                                                                                                                                                                                                                                                             |     |    |
| <p>Both tool boxes will have internal led lights with on /off switch controlled by</p>                                                                                                                                                                                                                                                                                                                                                                                              |     |    |
| <p>Doors opening and closing.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                   |     |    |
| <p>A tool rake mounted to the side of passenger tool box to hold 1- shovel 2- fire rakes.</p>                                                                                                                                                                                                                                                                                                                                                                                       |     |    |
| <p><b>CROSSLAY</b></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     |    |
| <p>.1.5" cross lay capable of holding 100 feet of 1.5" hose</p>                                                                                                                                                                                                                                                                                                                                                                                                                     |     |    |
| <p>2- 1.5" x 50ft fire hose, 1- 1 1.5" selectable nozzle w/ foam tube</p>                                                                                                                                                                                                                                                                                                                                                                                                           |     |    |
| <p>Cross lay mount on the top of driver side tool box.</p>                                                                                                                                                                                                                                                                                                                                                                                                                          |     |    |
| <p></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |     |    |
| <p></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |     |    |
| <p></p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |     |    |

|                                                                                                                                                                                                                  | YES | NO |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----|
| <b>INSIDE THE CAB</b>                                                                                                                                                                                            |     |    |
| Remove center seat and install center console to install the following in:                                                                                                                                       |     |    |
| 100 watt siren                                                                                                                                                                                                   |     |    |
| 6 position switch box control                                                                                                                                                                                    |     |    |
| Mounting bracket with 4 position                                                                                                                                                                                 |     |    |
| Mount Fire Department radio with antenna (radio and antenna will be supplied)                                                                                                                                    |     |    |
| 2- Streamlight, Vulcan LED flashlights with charger or equivalent.                                                                                                                                               |     |    |
| 100 watt speaker mounted on front bumper                                                                                                                                                                         |     |    |
| Tank level indicator                                                                                                                                                                                             |     |    |
|                                                                                                                                                                                                                  |     |    |
| <b>ON THE BED</b>                                                                                                                                                                                                |     |    |
| A baffled water tank 46" wide by 48" long by 36" tall built of plastic or fiberglass. (No metal tanks will be considered unless constructed of stainless steel).                                                 |     |    |
| The tank shall also have a 10 gallon foam tank built into the main tank. An equivalent stand-alone foam tank shall be considered.                                                                                |     |    |
| The fill openings for the water and foam will both be located at the top front of the tank so as to be easily accessible from the walkway on the bed.                                                            |     |    |
| The tank shall have sight glasses on the front of the tank so the water and foam volumes are visible from the walkway.                                                                                           |     |    |
| The water tank shall have a sight glass on the rear of the tank to be visible from the rear of the truck.                                                                                                        |     |    |
| The tank shall be equipped with a 3" connection located on the rear of the tank in a location that is suitable to attach the suction line for the fire pump.                                                     |     |    |
| There shall be a full port 2 1/2 valve located between the tank and fire pump and also another full port 2 1/2 valve located between the fire pump and rear of truck bed to be used for ground fill or drafting. |     |    |
|                                                                                                                                                                                                                  | YES | NO |
| The tank shall have a 1" connection (bypass line) provided on the top rear of the tank to be plumbed into a full port 1" ball valve located on the discharge header of the fire pump.                            |     |    |
| The tank shall be equipped with a 2" outlet located as low as practical on the rear of the tank to provide a drain point.                                                                                        |     |    |
| A discharge header shall be designed and constructed to contain enough openings to supply the 1" hose reel, 1" and 1 1/2" valve, 1" bypass line, and 1" whip line located on the front of the truck bed.         |     |    |
| The pump discharge plumbing shall have a foam inductor installed so that foam is available to all discharge points.                                                                                              |     |    |
| The foam inductor shall be plumbed to the foam tank with the appropriate valves.                                                                                                                                 |     |    |

|                                                                                                                                                                                                                                                                                                                                       |  |  |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| ALL discharge openings shall be equipped with a valve so that each discharge point can be isolated without affecting any of the other functions.                                                                                                                                                                                      |  |  |
| 2- 1" whip line shall be supplied and located on the walkway of the truck bed. With 2- 1" selectable gallon nozzles                                                                                                                                                                                                                   |  |  |
| The whip line shall be plumbed to the center, top of the water tank and be equipped with a valve and a swivel connection.                                                                                                                                                                                                             |  |  |
| A 19" diameter by 46" long hose reel with electric rewind shall be supplied by the bidder. Hose reel will be mounted on top of the water tank                                                                                                                                                                                         |  |  |
| The hose will exit from the sides of the truck, not the rear.                                                                                                                                                                                                                                                                         |  |  |
| Bidder shall furnish and install suitable heavy gauge electrical cable to provide power to the pump motor and hose reel.                                                                                                                                                                                                              |  |  |
| The maximum amount of 1" red line shall be installed on the hose reel, and with a 1" selectable gallon nozzle                                                                                                                                                                                                                         |  |  |
| The hose reel shall be equipped with 2 hose guides.                                                                                                                                                                                                                                                                                   |  |  |
| A rewind button shall be placed to allow a one person operation of the hose reel.                                                                                                                                                                                                                                                     |  |  |
| The pump panel will contain all the pump controls, start/stop switch, idle control, choke, oil pressure light and pump outlet pressure gauge. The pump panel will also contain the foam proportioned controls. The panel will be tilted to provide a direct view of all operations which will be located to operate from the walkway. |  |  |
| Pump shall be a Waterax B2X-18, 300 GPM, 2 stage, air cooled, belt driven or equivalent, and 12 volt battery. Supplied with its own separate fuel tank.                                                                                                                                                                               |  |  |
| <i>Note: Bidder shall list any proposed changes on vendor statement.</i>                                                                                                                                                                                                                                                              |  |  |
| <b>EMERGENCY LIGHTING</b>                                                                                                                                                                                                                                                                                                             |  |  |
| ALL lighting shall be high intensity LED.                                                                                                                                                                                                                                                                                             |  |  |
| The light bar shall be a 47" bar with red and blue lights capable of multiple patterns.                                                                                                                                                                                                                                               |  |  |
| Light bar will be permanent mounted on headache rack                                                                                                                                                                                                                                                                                  |  |  |
| The light bar shall be equipped with takedown and alley lights.                                                                                                                                                                                                                                                                       |  |  |
| TOTAL of 12 LED red and blue combination mini lights shall be installed on the side of the cab, front of the truck bed near the walkway to be visible from the side of the truck, rear of the truck bed to be visible from the side of the truck and on the front bumper to be visible from the side of the truck.                    |  |  |
| Want light to be placed to match our current brush trucks                                                                                                                                                                                                                                                                             |  |  |
| 1-42" LED clear working light mount on cab 1- 24" LED clear working light on grill guard                                                                                                                                                                                                                                              |  |  |
| Clear LED work lights shall be installed on the, sides and rear of the truck. Two work lights on each side of the truck along with, two on the                                                                                                                                                                                        |  |  |

|                                                                                                                                                                                                                                                             |  |  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|
| rear shall be used to provide adequate illumination for a safe work environment. Protection from damage shall be considered when choosing light mounting points.                                                                                            |  |  |
| ALL wiring shall be done using recommended wire sizes and industry best practices. Lights shall be wired with independent switches so that the operator can choose from side, front or rear for the emergency red and blue lighting.                        |  |  |
| The work lights shall be wired with individual switches so the operator can choose from front, rear, left or right.                                                                                                                                         |  |  |
| The takedown and alley lights in the light bar shall be wired to the appropriate work light switch.                                                                                                                                                         |  |  |
| The rear work lights shall be wired into the OEM truck backup light circuit to provide additional lighting when backing the truck. A DOT approved backup alarm shall be provided by the bidder and installed.                                               |  |  |
| <b>MISCELLANEOUS</b>                                                                                                                                                                                                                                        |  |  |
| <b>PM400 vhf radio and antenna, Lettering and 4" reflective striping on both sides. Must match other rigs owned by Stonewall FD</b>                                                                                                                         |  |  |
| ALL valves, controls and switches shall be labeled with their purpose and function.                                                                                                                                                                         |  |  |
| ALL piping or other steel components shall be painted or otherwise protected from rust or corrosion.                                                                                                                                                        |  |  |
| The bidder shall provide all wiring, bolts, nuts, piping and any other hardware or miscellaneous items needed to accomplish the construction of this wildland fire unit that is not specifically listed as being provided by the Stonewall Fire Department. |  |  |
| <b>The bidder shall provide an unconditional one year installation and workmanship warranty.</b>                                                                                                                                                            |  |  |
| <b>The bidder shall have 120 days from the delivery of the truck to complete the installation. <u>TIME IS OF THE ESSENCE</u></b>                                                                                                                            |  |  |
| <b>FOR EACH DAY PAST THE 120 DAY DEADLINE, A \$100 PER DAY PENALTY WILL BE DEDUCTED FROM THE FINAL PAYMENT.</b>                                                                                                                                             |  |  |
| <b>Reasonable consideration will be given for delays obviously beyond the bidder's control. Bidder shall contact the Fire with any reasons for the delay.</b> Chief Danny Summers 580.310.5916                                                              |  |  |

*Bidder shall furnish in writing in the vendor's proposal of the equipment proposed strictly meets these specifications. If no, please list each variation in the Vendor's Statement.*

**VENDOR'S STATEMENT:**

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

---

DEALER \_\_\_\_\_ DATE \_\_\_\_\_

ADDRESS \_\_\_\_\_

SIGNATURE \_\_\_\_\_ PHONE \_\_\_\_\_